

STEAM 6



OIL & GAS

Steam



APPLICATIONS

Low pressure steam hose.

TECHNICAL DESCRIPTION

Inner tube: synthetic EPDM rubber, black, smooth.

Reinforcement: synthetic textile.

Cover: synthetic EPDM rubber, black, fabric impression.

Temperature range: -30°C to +164°C.

Electrical properties: $R < 1M\Omega/lg$.

STANDARD/APPROVAL

EN ISO 6134:2017 type 1 class A.



**OIL & GAS****STEAM 6**

ID mm	OD mm	WORKING PRESSURE bar	BURSTING PRESSURE bar	BENDING RADIUS mm	WEIGHT kg/m	LENGTH m	ARTICLE NUMBER	STOCK () or min. order m
19.0 ±0.5	33.0 ±1	6	60	190	0.69	40	5513647	1
25.0 ±0.5	40.0 ±1	6	60	250	0.96	40	5513648	1
32.0 ±0.5	48.0 ±1	6	60	320	1.26	40	5513649	2
38.0 ±0.5	54.0 ±1.2	6	60	380	1.45	40	5513650	2
51.0 ±0.7	69.0 ±1.4	6	60	500	1.86	40	5513651	400

Tolerance on length: ±1% (ISO 1307 Standard).

☒ Upon availability.

**TRELLEBORG**