



## Airform PLW 20

Inwendig SBR  
Kleur Zwart  
Uitwendig SBR  
Kleur Zwart

Innen SBR  
Farbe Schwarz  
Außen SBR  
Farbe Schwarz

Inside SBR  
Colour Black  
Outside SBR  
Colour Black

Perslucht / waterslang voor industriële toepassingen

- In- en uitwendig glad
- Flexibel en knikvast
- Weerbestendige en slijtvaste buitenwand
- Europees product

Pressluft / Wasserschlauch für industriellen Einsatz

- Innen und aussen glatt
- Flexibel - und knickfest
- Abrieb- und witterungsbeständige Decke
- Europäisches Markenprodukt

Compressed air / water hose for industrial applications

- Smooth tube and cover
- Kink resistant and flexible
- Abrasion and weather resistant cover
- Made in EU

Binnen Innen Inside ø mm	Buiten Aussen Outside ø mm	Buigstr. Biegerad. Bendrad. mm	Vacuüm Vakuum Vacuum Bar	Gewicht Gewicht Weight gr/m	Werkdruk Betriebsdruck Work. press. Bar
6.0	12.0	60.0	0	110	20
8.0	15.0	80.0	0	170	20
10.0	17.0	100.0	0	220	20
13.0	21.0	75.0	0	280	20
16.0	26.0	100.0	0	390	20
19.0	30.0	120.0	0	490	20
20.0	30.0	200.0	0	450	20
25.0	35.0	150.0	0	630	20
32.0	44.0	200.0	0	1070	20

Normen / Standards  
ISO R 1307

Temperatuurbereik (Zie medium)  
Temperatuurbereik (siehe Medium)  
Temperature range (see media)  
-30 °C +70 °C

Werkdruk	Barstdruk
Betriebsdruck	Platzdruck
Working pressure	Burst pressure
20 bar	60 bar

Markering / Markierung / Branding:  
OPTIMIT AIR WATER WP20 BAR ISO 1307 -  
[ID MM] - MADE IN EU

Lengten / Längen / Lengths  
40 / 50 / 100 m  
Kan per diameter verschillen / Kann je nach  
Durchmesser variieren / Can vary per  
diameter



-2023-

