



Universal P12

Inwendig SBR
Kleur Zwart
Uitwendig SBR
Kleur Zwart

Innen SBR
Farbe Schwarz
Außen SBR
Farbe Schwarz

Inside SBR
Colour Black
Outside SBR
Colour Black

Universele water- en luchtslang

Geschikt voor water 80 °C tot max. 12 bar, perslucht tot 10 Bar, logen en chemicaliën

- Bestendig tegen oliesporen
- Uitwendig slijtvast en weerbestendig

Industrieller Luft- und Wasserschlauch

Geeignet für Wasser 80 °C bis max. 12 Bar, Pressluft bis 10 Bar, Laugen und Chemikalien

- Beständig gegen Ölsuren
- Decke abrieb und witterungsbeständig

Industrial air and water hose

Suitable for water 12 Bar max. 80 °C, pressurized air 10 Bar, bases and chemicals

- Tube resistant to effect of oil mists
- Abrasion and weathering resistant cover

Binnen Innen Inside ø mm	Buiten Aussen Outside ø mm	Buigstr. Biegerad. Bendrad. mm	Vacuüm Vakuum Vacuum Bar	Gewicht Gewicht Weight gr/m	Werkdruk Betriebsdruck Work. press. Bar
25.0	34.0	250	0	600	12
28.0	38.0	290	0	680	12
30.0	41.0	300	0	1020	12
32.0	42.0	320	0	1080	12
35.0	47.0	350	0	1160	12
38.0	49.0	380	0	1450	12
40.0	54.0	400	0	1510	12
45.0	59.0	450	0	1820	12
48.0	62.0	480	0	1880	12
51.0	64.0	500	0	1950	12
55.0	69.0	580	0	2030	12
63.0	79.0	630	0	2350	12
70.0	86.0	700	0	2600	12
76.0	91.0	760	0	2780	12
80.0	96.0	800	0	2950	12
90.0	106.0	900	0	3150	12
102.0	118.0	1020	0	3450	12
110.0	128.0	1100	0	3910	12
127.0	145.0	1270	0	4820	12
152.0	170.0	1520	0	5830	12

Normen / Standards
ISO R 1307

Temperatuurbereik (Zie medium)
Temperatuurbereich (siehe Medium)
Temperature range (see media)
-25 °C +90 °C

Werkdruk Barstdruk
Betriebsdruck Platzdruck
Working pressure Burst pressure
12 bar 40 bar

Markering / Markierung / Branding:
UNIVERSAL AIR WATER WP 12 BAR

Lengten / Längen / Lengths
20 / 40 m

Kan per diameter verschillen / Kann je nach Durchmesser variieren / Can vary per diameter