

# SUPERVRAC



**BULK MATERIALS  
HANDLING**

Bulk tank truck discharge



## APPLICATIONS

Pneumatic transport of bulk abrasive products.  
Discharge from road and rail tankers and delivery to storage bins (cement, sand, limestone, coal, etc.).

## ADVANTAGES

- † Light weight, flexible hose that coils flat.
- † Excellent resistance to abrasion.
- † Static conductive tube.

## TECHNICAL DESCRIPTION

Inner tube: wear resistant NR, black, smooth.

Reinforcement: synthetic textile.

Cover: weather resistant NR, black, fabric impression.

Temperature range: -30°C to +90°C.

Electrical properties: conductive tube and cover,  
 $R < 10^6 \Omega/m$ .



RAC




Made in Portugal



TRELLEBORG

SUPERVRAC





ID mm	WALL THICKNESS mm	OD mm	WORKING PRESSURE bar	BURSTING PRESSURE bar	WEIGHT kg/m	LENGTH m	ARTICLE NUMBER	STOCK ( ) or min. order m
75.0	6.75 ±1.25	88.5 ±2.0	7	21	1.83	20	0060675	120
75.0	6.75 ±1.25	88.5 ±2.0	7	21	1.83	40	0060674	120
75.0	9 ±1.00	93.0 ±1.5	7	21	2.75	20	0060189	∅
75.0	9 ±1.00	93.0 ±1.5	7	21	2.75	40	0060193	∅
89.0	6.25 ±1.25	101.5 ±2.0	7	21	2.07	20	0060682	∅
89.0	6.25 ±1.25	101.5 ±2.0	7	21	2.07	40	0060683	∅
100.0	6 ±1.00	112.0 ±1.5	7	21	2.4	20	0129701	120
100.0	6 ±1.00	112.0 ±1.5	7	21	2.4	40	0129702	120
100.0	9 ±1.00	118.0 ±1.5	7	21	3.58	20	0060194	∅
100.0	9 ±1.00	118.0 ±1.5	7	21	3.58	40	0060195	∅
110.0	6.5 ±1.25	123.0 ±2.0	7	21	2.71	20	0060684	∅
110.0	6.5 ±1.25	123.0 ±2.0	7	21	2.71	40	5006696	200
127.0	8.5 ±1.25	144.0 ±2.0	7	21	4.2	20	0060685	120
127.0	8.5 ±1.25	144.0 ±2.0	7	21	4.2	40	0060686	∅
152.0	8.5 ±1.25	169.0 ±2.0	7	21	5	20	0060689	120
152.0	8.5 ±1.25	169.0 ±2.0	7	21	5	40	0060690	120

Tolerance on length: ±1% (ISO 1307 Standard).

∅ Upon availability.

Digital version

