

## Flamex B se

PU Suction Hose & Transport Hose, lightweight and flexible, hardly inflammable acc. to DIN 4102 B1



Technical Drawing



Connections



Construction



### Material

- spiral: spring steel wire
- wall: pure polyester polyurethane with flame-retardant additives (acc. to DIN ISO 4649 more abrasion-resistant than polyether polyurethane)
- wall thickness between spirals approx. 0.7 mm

### Applications

- Shavings extractions in wood processing
- Hardly inflammable transport hose for abrasive solids
- Wood processing machines
- Protective hose against mechanical wear

### Properties

- acc. to DIN 26057
- hardly inflammable acc. to DIN 4102 B1
- acc. to requirements of the Holz-BG standard, BGI 739-2
- very light
-



280	0,25	0,05	290	290	2,6	000198:280:x	/	25
300	0,23	0,05	310	310	3,2	000198:300:x	/	20
315	0,23	0,05	325	325	3,32	000198:315:x	/	20
325	0,23	0,05	335	335	3,4	000198:325:x	/	20
350	0,12	0,05	360	360	3,6	000198:350:x	/	20
400	0,12	0,05	410	411	4,45	000198:400:x	/	20
450	0,12	0,05	460	461	5,06	000198:450:x	/	20
500	0,12	0,04	510	511	5,7	000198:500:x	/	20

All data refers to a medium and ambient temperature of +20 °C.

\* Refers to the inner hose lining

Subject to technical changes and colour deviations.

#### Available on request

- Available on request in other lengths, sizes and colours, with print.